



LIQUIDYNAMICS™

FLUID HANDLING
TECHNOLOGY

DEF HEAVY DUTY 4 WHEEL CART WITH GAS ENGINE, RESALE METER, REEL

This is an ideal solution for a portable DEF bulk transfer system. It has an on board Weights and Measures approved meter with ticket printer and air eliminator, one micron filtration, 1" x 50' hose reel and a gasoline engine driven DEF pump rated at 40 GPM. The compact 4 wheel cart allows ultimate flexibility in positioning when transferring DEF from totes or bulk tanks.

The heavy duty 4 wheel cart is powder coated to ensure durability and long life. The cart has two large 10" fixed wheels and two swivel wheels with a total load rating of 2,400 lb. Swivel wheels are fitted with brakes to secure the cart in position as necessary.

A 4 HP gas engine driven, self-priming centrifugal pump provides approximately 35 GPM system flow rate. All wetted components are stainless steel, polypropylene and EPDM in conformance with ISO 22241 specifications. Pump inlet fitting has a 1½" Dry-Mate fitting for ease of connection and spill prevention.

P/N **33381DEF**

DEF Heavy Duty 4 Wheel Cart w/Gas Engine, Resale Meter, Filter and Reel. Order optional suction hose from choices below. Optional hose set includes Dry-Mates for connection to cart on one side and 1½" NPTF other side.



P/N **81242C-10**

1½" x 10' DEF Suction Hose with male Dry-Mate x 1½" NPTM.

P/N **81242C-15**

1½" x 15' DEF Suction Hose with male Dry-Mate x 1½" NPTM.

P/N **81242C-20**

1½" x 20' DEF Suction Hose with male Dry-Mate x 1½" NPTM.

Dry-Mates used to connect suction hose to IBC tote bottom fitting.

P/N **900580A**

1½" female Dry-Mate x 1½" NPTF

P/N **900581**

2" male Dry-Mate x 2" NPTF

