

AIR OPERATED GREASE PUMPS



Part Number	11148T	11174T	11195T	11348	11374	11395	11595	11748	11848
Pump Ratio	60:1	60:1	60:1	80:1	80:1	80:1	35:1	10:1	13:1
Delivery Rate (oz/min)	48	48	48	126	126	126	140	70 lb/min	100 lb/min
Working Pressure PSI	80-120	80-120	80-120	80-120	80-120	80-120	80-120	80-145	80-145
Air Inlet (NPTF)	1/4"	1/4"	1/4"	3/8"	3/8"	3/8"	3/8"	3/8"	3/8"
Grease Outlet (NPTF)	*1/4"	*1/4"	*1/4"	3/4"	3/4"	3/4"	3/4"	1"	1 1/2"
Air Consumption (cfm)	12	12	12	20	20	20	20	87	103
Noise (dB)	79	79	79	79	79	79	79	79	79
Drum Size (lb)	30/60	120	420	30/60	120	420	420	N/A	N/A
Dia., Suction Tube (in)	1.26	1.26	1.26	1.42	1.42	1.42	1.65	2.00	3.00
Length Suction Tube (in)	19.75	29.50	37.50	19.75	29.50	37.50	37.5	N/A	N/A
Shipping Weight (lb)	12	14	16	20	22	24	26	32	40

Note: For longer pump life and efficiency, we recommend the use of dried air or an air filter. As with any pneumatic equipment, you can expect longer trouble free operation with the use of clean, dry air. The use of an air drier, separator (filter), or minimally an air filter is advantageous. See page 11 for selection of air regulators, separators (filter) and dryers.

*Order with a "-02" suffix (eg; 11174T-02) to receive 3/8" discharge.