

PNEUMATIC OIL PUMPS



Part Number (w/o Bung Adapter)	21100T	21073T	21094T	21200	21300	21400	21500
Part Number (w/ Bung Adapter)	21100T-S2	21073T-S2	21094T-S2	21200-S1	21300-S1	21400-S2	21500-S2
Ratio	5:1	5:1	5:1	5:1	5:1	8:1	13:1
Flow Rate @ 90 PSI (GPM)	5	5	5	8	11	5.5	4.0
Maximum Air Pressure (PSI)	120	120	120	120	120	120	120
Air Inlet Size	1/4" NPT	1/4" NPT	1/4" NPT	3/8" NPT	3/8" NPT	3/8" NPT	3/8" NPT
Fluid Inlet Size	1" NPTF	1" NPTF	1" NPTF	1 1/2" NPTF	1 1/2" NPTF	1" NPTF	1" NPTF
Fluid Outlet Size	1/2" NPTF	1/2" NPTF	1/2" NPTF	3/4" NPTF	3/4" NPTF	3/4" NPTF	3/4" NPTF
Noise	79 db	79 db	79 db	79 db	79 db	79 db	79 db
Air Consumption (cfm)	12	12	12	18	21	21	22
Suction Tube Diameter	1.65"	1.65"	1.65"	2"	2"	2"	2"
Suction Tube Length	11"	29"	37"	15"	17"	11"	11"
Fits Drum Sizes (Gal.)	Universal	16/30	55	Universal	Universal	Universal	Universal
Shipping Weight, lbs.	12	14	16	19	21	22	24

Note: For longer pump life and efficiency, we recommend the use of dried air or an air filter. As with any pneumatic equipment, you can expect longer trouble free operation with the use of clean, dry air. The use of an air drier, separator, or minimally an air filter, is advantageous. See page 11 for our selection of air regulators, separators (filter) and dryers.