

## ELECTRIC OIL PUMPS WITH SPIGOT – 115 VAC

These 115 VAC Electric Spigot Pumps provide a continuous, smooth stream of fluid and eliminate the pulsations and splashing created by air operated piston or diaphragm pumps. Applications include dispensing of motor oil, gear oil, cutting oil,

ATF, hydraulic fluid, 100% antifreeze and similar fluids. These pumps may be mounted vertically on a 55 gallon drum or horizontally on a tank or wall bracket.



P/N **33221-S1**  
 Versatile horizontal mount system has excellent priming capability. Ideal for use with deep tanks and wall mount systems. Inlet fitting is 3/4" NPTF.



P/N **33221-S3**  
 Vertical mount system includes 3.0 GPM electric pump, spigot, 2" double tap, 1"x30" suction pipe and foot valve. Ideal for use with 55 gallon drums and bench tanks.

Part Number	Description	P by-pass	Amps	HP	Shipping Weight	Inlet Dimensions	Discharge Dimensions
33221	2.5 GPM, 170 PSI Max, Manual Shut-off	240	15	1.2	33 lbs.	3/4"	3/4"
33222	4.0 GPM, 230 PSI Max, Manual Shut-off	325	13	2.0	44 lbs.	3/4"	3/4"
33223	20 GPM, 40 PSI Max, Manual Shut-off	80	18	2.0	73 lbs.	1"	1"
33250	7.0 GPM, 80 PSI Max, Manual Shut-off	80	13	1.6	34 lbs.	3/4"	3/4"
560086	2.5 GPM, 650 PSI Max, Manual Shut-off	650	16	1.5	71 lbs.	1"	3/4"
560087	2.5 GPM, 450 PSI Max, Manual Shut-off	450	12	1.0	63 lbs.	1"	3/4"
560088	4.5 GPM, 200 PSI Max, Manual Shut-off	200	12	1.0	60 lbs.	1"	3/4"
560089	9.0 GPM, 200 PSI Max, Manual Shut-off	200	18	2.0	65 lbs.	1"	3/4"