

## USED OIL TANKS

### P/N 901076-CH

300 Gallon Used Oil Tank for bulk storage, has convenient hatch opening with cover to allow filter elements to be drained prior to disposal. Hatch opening is also handy for emptying small containers of used oil. Tank has two 2" bung openings along with a 1" drain.

Dimensions: 37.5" dia. x 63" long x 45" max height at chute handle. Chute opening, 21½" x 14¼" x 6¾" deep.



### P/N 901076-12

Used Oil Pump/Tank kit includes 300 gallon chute tank P/N 901076-CH shown above along with a 3/4" double diaphragm pump, 3/4" x 12' suction hose with dry break disconnect and 4 way valve system that allows the operator to evacuate portable oil drains via the suction valve position, or empty the tank by simply selecting the discharge valve position on the 4 way valve. A tank level gauge is also included to allow monitoring of fluid level along with an air filter/regulator to control pumping rate.

Dimensions: 37.5" dia x 63" long x 58" max height at pump.



### P/N 950027-55

3/4" D.D. Pump w/vertical inlet manifold kit to fit 55 gallon drum. Kit includes "close" nipple, suction pipe and double tap with 3/8" return port for use with thermal expansion valve kit.

### P/N 950027-275

3/4" D.D. Pump w/vertical inlet manifold to fit 275 gallon tank. Has 44" long suction pipe, "close" nipple and double tap with 3/8" return port for use with thermal expansion valve kit. Schedule 80 PVC suction pipe can easily be trimmed to fit shorter tank depths.



### P/N 970023-225

225 gallon bench tank with 3/4" double diaphragm pump and 4 way valve system can be used to evacuate portable oil drains in the suction valve position (fills the tank) and then the tank can be emptied by positioning the valve to the discharge position. System includes an air filter/regulator, 3/4" x 12' suction/discharge hose with dry break disconnect, tank level gauge and lockable fill cap. The bench tank provides a convenient work surface in shops where space is a premium.

Dimensions: 48" x 33" x 39" H